Lifetime Guarantee



Thank you for purchasing this instrument from Intellitronix. We value our customers!

INSTALLATION GUIDE

LED Digital Oil Temperature Gauge Part Number: M9108

* Always disconnect the battery before attempting any electrical work on your vehicle.*

KIT COMPONENTS

Digital Oil Temperature Gauge: Displays 50 – 350° F. range

Temp Sender Unit (S8013)

Mounting equipment

WIRING INSTRUCTIONS

Note: Automotive circuit connectors are the preferred method of connecting wires. However, you may solder if you prefer.

Ground – Black--This is the main ground for the display system. A wire should be run from this board to the vehicle engine block for the best ground. Use 18 AWG or larger wire to ensure sufficient grounding. Proper vehicle grounding is extremely important for any gauges (or electronics) to operate correctly. The engine block should have heavy ground cables to the battery, frame, and firewall. Failure to properly ground the engine block, senders, or digital dash can cause incorrect or erratic operation.

Battery Red--Connect the +12 Volt terminal to constant +12V power from the battery. Use 18 AWG wire to **Battery** Red--Connect the +12 Volt terminal to constant +12V power from the battery. Use 18 AWG wire to ensure the system receives a sufficient power feed

Dimmer-Purple Connect to the parking lights to dim the LEDs 50% when the headlights are on. However, ***DO NOT** * connect to the headlight rheostat control wire, or the dimming feature will not work properly and may cause damage to Unit.

Temperature - **Blue** Connect to the output of the temperature sending unit. **Do not** use Teflon tape or other sealer on the new sending unit's threads to avoid inaccurate readings



Technical Support

Monday – Friday 9am to 5 pm EST (440) 359 7200

support@intellitronix.com

CHECK OUT THE SUPPORT PAGE AT

www.intellitronix.com

FOR QUICK ANSWERS (Q&A) TO YOUR QUESTIONS



This product carries a limited Lifetime Warranty.

This warranty is limited to replacement or repair of the unit at the discretion of Intellitronix.

RETURN POLICY PROCEDURES

Return Policy Instructions

- 1. Download the Intellitronix Return/Repair Form and fill in the information on the form about the product.
- 2. Place the product being returned in the original packaging that it came in and include a copy of the completed Intellitronix Return/Repair Form.
- 3. All packages must be accompanied with an RMA Number.
 - Please call Technical Support at +1 440-359-7200 to receive an RMA Number.
- 4. Mail the product being returned with the completed Return/Repair Form and a copy of the original sales invoice.

Request for Product Refund

- 1. All returns for a refund must have a completed Intellitronix Return/Repair Form included in the package with the returned product.
- 2. If the return is for a product that is not defective a 20% restocking fee will be charged. The product must be in the same pristine condition that it was sent to you.
- 3. Proof of purchase is required. Please include a copy of the original sales order with the returned product.
- 4. All product must be returned undamaged and in working order in the original packaging including plexiglass, sending units, mounting hardware, or you will be subject to additional charges for product and accessories not returned.
- 5. All refunds will be reviewed by the Accounting Office.